

BLENDER & FREEZER CONFIGURATION OPTIONS



B6 BLENDER

Self-Sanitizing (Sold Separately)

FR00-0106 \$12,375



BLENDING BAR

Our Best Seller 180 Cup Capacity

FR10-0011 \$17,175

On-Counter Configuration



MINI BLENDING BAR

Good for Medium Traffic **Smaller Footprint**

FR10-0011-M \$16,600

On-Counter Configuration



DOUBLE BLENDING BAR

Allows for Dual Blending Supports High Foot Traffic

> FR10-0011-DH \$29,800

On-Counter Configuration



TALL UPRIGHT FREEZER

Highest Cup Capacity Good for Limited Storage

\$18,275 FR10-0022-RH

Free Standing Configuration



SINGLE DOOR FREEZER

Best Selling Blender And Compact Freezer

FR10-0007-RHC \$16,275

Free Standing Configuration



SIDE COUNTER

Optional Storage (Sold Separately)

\$1,375 FR10-SCTR

EQUIPMENT SPECIFICATIONS & INSTALLATION REQUIREMENTS

FREEZERS	W"	D"	Н"	CUP CAPACITY	FACINGS	EMPTY WEIGHT	FULL WEIGHT	PRICE (CAD)
MINI BLENDING BAR	33.5"	32.5"	56"	90	15	225 LBS	295 LBS	\$4,225
BLENDING BAR	45.5"	32.5"	56"	180	30	245 LBS	385 LBS	\$4,800
DOUBLE BLENDING BAR	61.5"	32.5"	56"	180	30	250 LBS	390 LBS	\$5,050
SINGLE DOOR FREEZER	28"	31"	32.5"	102	18	200 LBS	280 LBS	\$3,900
TALL UPRIGHT FREEZER	30"	29.5"	78.5"	252	42	365 LBS	560 LBS	\$5,900
SIDE COUNTER	16"	26"	36"	-	-	-	_	\$1,375

BLENDER SPECS*

DIMENSIONS: 15.25" W / 25" D / 42" H WEIGHT: 125 LBS

CERTIFICATIONS: NSF, TÜV, SUD *Add the dimensions of desired freezer to the dimensions of the blender when planning for necessary equipment space.

INSTALLATION REQUIREMENTS

- REQUIRES A DEDICATED 15A, 120V CIRCUIT
- 7 FT. GROUNDED POWER CORD (INCLUDED) 150 PPM TDS FREEZERS REQUIRE SEPARATE 15A CIRCUIT
- FROM BLENDERS
- GRAVITY DRAIN REQUIRED
- BLENDER COMES WITH 10 FT LENGTH OF 3/4" ID ANTI-MICROBIAL DRAIN TUBE

FILTERED

- · CONNECT THE 3/8" INNER DIAMETER WATER SUPPLY LINE** WITH THE HOSE CLAMP PROVIDED TO THE WATER LINE AT THE BACK OF THE BLENDER
- TURN THE BALL VALVE LEVER PARALLEL TO THE WATER TO INITIATE WATER FLOW
- ENSURE THE WATER SUPPLY LINE IS FILTERED TO 120 PPM HARDNESS AND
- REGULATE THE LOCATION'S WATER PRESSURE TO 25-50 PSI
- **CUSTOMER PROVIDES WATER SUPPLY LINE